



MATERIAL SAFETY DATA SHEET

Page 1 of 7

HE403C - SPRAYGRADE COLD-AP CEMENT

1. Product And Company Identification			
Supplier HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com		Manufacturer HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com	
Supplier Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666		Manufacturer Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	
 Issue Date: 02/25/2011 Product Name: HE403C - SPRAYGRADE COLD-AP CEMENT Product Code: HE403C			
2. Composition/Information On Ingredients			
Ingredient Name		CAS Number	Percent Of Total Weight
1,2,4-trimethylbenzene		95-63-6	0.1 - 1
petroleum asphalt		8052-42-4	30 - 50
attapulgite		12174-11-7	5 - 15
calcium carbonate		1317-65-3	10 - 20
silica, quartz		14808-60-7	0.1 - 1
stoddard solvent		8052-41-3	20 - 30
xylene		1330-20-7	0.1 - 1
EMERGENCY OVERVIEW			
WARNING! Combustible Liquid. Central nervous system depressant. Vapor may cause light-headedness, headache, nausea, loss of coordination and respiratory tract irritation. Causes skin irritation.			
Appearance/Odor: Black liquid, strong petroleum solvent odor			
3. Hazards Identification			
Primary Routes(s) Of Entry Inhalation			
Eye Hazards May cause eye irritation (burning, tearing, redness or swelling).			
Skin Hazards May cause skin irritation and contact dermatitis upon prolonged contact. Dermal sensitization may occur from repeated and prolonged exposures.			
Ingestion Hazards May be harmful if swallowed. May cause gastric distress, vomiting and diarrhea.			



HE403C - SPRAYGRADE COLD-AP CEMENT

3. Hazards Identification - Continued

Inhalation Hazards

Exposure to vapors, dusts or mists may cause respiratory tract irritation. Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.

Chronic/Carcinogenicity Effects

This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

Remove contaminated clothing and shoes. Wash affected areas with soap and water.

Ingestion

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim. Call a physician or poison control center immediately.

Inhalation

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately.

Note To Physician

Aspiration of liquid into the lungs during swallowing or vomiting can cause lung inflammation, serious lung damage and even death from chemical pneumonitis.

5. Fire Fighting Measures

Flash Point: 105 °F 45.5 °C

Flash Point Method: Closed Cup

Flammability Class: Class II

Lower Explosive Limit: 0.9

Upper Explosive Limit: 6.0

Fire And Explosion Hazards

Combustible Liquid. Vapors are heavier than air and may spread long distances and ignite. Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Extinguishing Media

Chemical foam, carbon dioxide (CO₂), or dry chemical. Do not use direct stream of water.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect and dispose in accordance with applicable regulations. Avoid runoff to waterways and sewers. For large spills, contain runoff and recover by pumping with explosion proof equipment.

7. Handling And Storage

Handling And Storage Precautions

Keep away from ignition sources. Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Do not handle or store near heat, sparks, flame, strong oxidants or strong acids. Use only with adequate ventilation.

HE403C - SPRAYGRADE COLD-AP CEMENT**8. Exposure Controls/Personal Protection****Engineering Controls**

Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.

Eye/Face Protection

Chemical splash goggles or faceshield over safety glasses or goggles recommended.

Skin Protection

Use with chemical-protective gloves to prevent skin contact.

Respiratory Protection

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

Ingredient(s) - Exposure Limits

1,2,4-trimethylbenzene

ACGIH TLV-TWA 25 ppm

petroleum asphalt

OSHA PEL-TWA 5mg/m³

ACGIH TLV-TWA 0.5mg/m³ (Benzene soluble aerosol)

calcium carbonate

OSHA PEL-TWA 15 mg/m³ (total dust)

OSHA PEL-TWA 5 mg/m³ (respirable dust)

silica, quartz

ACGIH TLV-TWA 0.025 mg/m³

OSHA PEL-TWA 30mg/m³ / (%SiO₂+2) (total dust)

OSHA PEL-TWA 10 mg/m³/ (%SiO₂+2) (respirable dust)

stoddard solvent

ACGIH TLV-TWA 100 ppm

OSHA PEL-TWA 500 ppm

xylene

ACGIH TLV-STEL 150 ppm

ACGIH TLV-TWA 100 ppm

OSHA PEL-TWA 100 ppm

9. Physical And Chemical Properties**Appearance**

Black liquid

Odor

Strong petroleum solvent odor

Chemical Type: Mixture

Physical State: Liquid

Boiling Point: 310-400 °F 154-204 °C

Specific Gravity: 1.10

Percent Volatiles: 33

Vapor Pressure: 2@68°F

HE403C - SPRAYGRADE COLD-AP CEMENT

9. Physical And Chemical Properties - Continued

Odor - Continued

Vapor Density: >1

pH Factor: not applicable

Solubility: insoluble in water

Evaporation Rate: <1

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatible Materials

Avoid contact with strong oxidizing agents and acids.

Hazardous Decomposition Products

Toxic and irritating gases, vapors or fumes, carbon monoxide (CO), carbon dioxide (CO₂).

11. Toxicological Information

Chronic/Carcinogenicity

IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): silica, quartz

ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz

NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz

Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

Miscellaneous Toxicological Information

Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

Ingredient(s) - Toxicological Data

1,2,4-trimethylbenzene

LD50 (oral, rat): 5000 mg/kg

LC50 (rat): 18 g/m³ (4-hour exposure)

calcium carbonate

oral-rat LD50: 6450 mg/kg

silica, quartz

iv-rat LD50: 500 mg/kg bw/Quartz (10-200 um)

stoddard solvent

oral-rat LD50: >5000 mg/kg

dermal-rabbit LD50: >3000 mg/kg

inhal-rat LC50: >5500 mg/m³ (880 ppm)

inhal-rat LC50: >1300 ppm

xylene

LD50 (oral, rat): 5400 mg/kg

LD50 (dermal, rabbit): 12180 mg/kg

LC50 (rat): 6350 ppm (4-hour exposure)

12. Ecological Information

No specific information available.

HE403C - SPRAYGRADE COLD-AP CEMENT

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Ground or Water Domestic Voyage

Not restricted if shipped in containers <450L (119 gallons)

Restricted if shipped in containers >450L (119 gallons)

US NA1993, Combustible liquid, n.o.s., (Petroleum Distillates mixture), Combustible liquid, III

Canada UN1999, Tars liquid, 3, III

Unless departs > flash point:

Both UN3256, Elevated Temperature liquid, flammable, n.o.s., (Petroleum Distillates mixture), 3, III

IMDG IMDG Code 2.3.2.5 - exempted from marking, labeling & testing of packages

IATA UN1999, Tars liquid, 3, III

DOT (Pictograms)



15. Regulatory Information

U.S. Regulatory Information

Asphalt may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.

Ingredient(s) - U.S. Regulatory Information

1,2,4-trimethylbenzene

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

xylene

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

Ingredient(s) - State Regulations

1,2,4-trimethylbenzene

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

petroleum asphalt

California - Proposition 65

attapulgit

California - Proposition 65

calcium carbonate

Pennsylvania - Workplace Hazard

silica, quartz

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

HE403C - SPRAYGRADE COLD-AP CEMENT

15. Regulatory Information - Continued

Ingredient(s) - State Regulations - Continued

California - Proposition 65
 Massachusetts - Hazardous Substance
 stoddard solvent
 New Jersey - Workplace Hazard
 Pennsylvania - Workplace Hazard
 Massachusetts - Hazardous Substance
 New York City - Hazardous Substance
 xylene
 New Jersey - Workplace Hazard
 New Jersey - Environmental Hazard
 New Jersey - Special Hazard
 Pennsylvania - Workplace Hazard
 Pennsylvania - Environmental Hazard
 Massachusetts - Hazardous Substance
 New York City - Hazardous Substance

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: B3 - Combustible Liquid, D2A - Very Toxic


Ingredient(s) - Canadian Regulatory Information

1,2,4-trimethylbenzene
 WHMIS - Ingredient Disclosure List
 silica, quartz
 WHMIS - Ingredient Disclosure List
 stoddard solvent
 WHMIS - Ingredient Disclosure List

WHMIS - Canada (Pictograms)



NFPA



HMIS

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	

16. Other Information

Revision/Preparer Information

This MSDS Supersedes A Previous MSDS Dated: 03/04/2008

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information



MATERIAL SAFETY DATA SHEET

Page 7 of 7

HE403C - SPRAYGRADE COLD-AP CEMENT

Disclaimer - Continued
for their particular purposes(s).